





# LEDECH

## **SWIMMING SYSTEM**

SSS - N20 - A

#### **EQUIPMENT**

#### 1. Race Starter (Model: STR-100) - 1 unit

Primary triggering device for start commands, ensuring standards-compliant, synchronized initiation. Fully compatible with the system controller and timing infrastructure.

#### 2. Touchpads (Model: ST-2490-F) — Quantity: equal to lane count

One finish-detection pad per lane, installed at each lane end. **Scaling:** The quantity increases or decreases according to the total number of lanes and the near/far-lane configuration.

#### 3. Lane Boxes (Model: SKL-LB-V1) — Quantity: equal to lane count

One interface/connection box per lane for sensor and cabling terminations. **Scaling:** The quantity increases or decreases according to the total number of lanes and the near/far-lane configuration.

#### 4.Thermal Printer (Model: SKL-EPS-T70) — 1 unit

Industrial-grade thermal printer for fast, quiet, low-cost printouts of race results and interim outputs.

#### 5. Swimming Timer (Model: SKL-SWC-V2) — 1 unit

Central controller for pool timing and sensor event management; coordinates the starter, touchpads, and scoreboard.

#### 6. Race Scoreboard (Model: SKL-SPL-X) — 1 unit


Lane-wise results/information display. **Scaling:** The number of display lines is configured to match the total number of lanes.

### 7. Starting Blocks — Qty: equal to lane count

- Configs: With or without False Start Detection (FSD).
- Heights: 40 cm with Riser (Open-Face) recommended per World Aquatics; 70 cm
  Stepped option.
- Integration: Compatible with SKL-DP-V1 (deck plate) and SKL-WJB (wall junction); terminations via deck plate.

#### **OPTIONAL EQUIPMENT**

- Event-heat-record, lap-length-time and team points scorebord modules can add to the scoreboard.
- Scoreboard can be produced with display size of 16,20,23,25 cm or 30 cm or according to display color as special.



Race Scoreboard (SKL - SPL - 8)



Swimming Timer (SKL - SWC - V2)



Lane Box (SKL - LB - V1)




Race Starter (STR – 100)





Thermal Printer (SKL-EPS-T70)



**TOUCHPAD (ST-2490-F)** 







+90 541 814 30 54 +90 541 845 30 54

